

GA SERIES COMBINATIONS

GAFC SERIES FR.L. COMBINATION & GAC SERIES F.R.L. COMBINATION

Benefits:

- Quick and reliable mounting clamps makes it convenient to install and use.
- The performance of pressure adjustment is reliable with high precision.
- The efficiency of eliminating moisture and solid grain is high.
- Two drain types are available: manual drain + semi-auto drain and automatic drain.
- Oil can be filled with supply pressure on
- Three bowl materials are available: PC, Metal and Nylon.



[GAC air preparation units 3D files Download](#) [GAFC air preparation units 3D files Download](#)

[GAC air preparation units brochure pdf Download](#) [GAFC air preparation units brochure pdf Download](#)

TECHNICAL DETAILS

Port size	GAC/GAFC200-06 : G1/8" GAC/GAFC200-08, GAC/GAFC300-08 & GAC/GAFC400-08: G1/4" GAC/GAFC300-10, GAC/GAFC400-10: G3/8" GAC/GAFC400-15: G1/2" GAC/GAFC600-20: G3/4" GAC/GAFC600-25: G1"
Filtering grade	40 µm or 5 µm
Pressure range	Putput pressure 1,5-9,0 bar Maximum supply pressure 10 bar
Recommended lubricant	ISO VG 32 or equivalent