

GAL LUBRICATOR

GA SERIES LUBRICATOR

Benefits:

- The structure of oil dripping adopts gap seal type, which makes the adjustment of oil supply more reliable
- Oil feed ring can only make on full turn. The quantity of oil supply basically takes on linear distribution
- The quantity of oil supply can be generally calculated according to the position of graduation ring
- Special drip nozzle structure will produce negative pressure in oil dripping outlet and the mist flow is minimal
- Three material of bowl are available: PC, Nylon and metal
- Oil bowl can be refilled while the lubricator is under pressure
- Large oil bowl
- The bracket can be selected for installation



[GAL lubricators 3D Files Download](#) [GAL lubricators brochure pdf Download](#)

TECHNICAL DETAILS

| | |
|-----------------------|--|
| Port size | GAL200-06: G1/8 GAL200-08, GAL300-08 & GAL400-08: G1/4 GAL300-10, GAL400-10: G3/8 GAL400-15: G1/2 GAL600-20: G3/4 GAL600-25: G1 |
| Pressure range | 0,5-1,0 bar |
| Recommended lubricant | ISO VG 32 or equivalent |
| Material | Oil bowl – Aluminium alloy\ PC\ Nylon Body of lubricator – Aluminium alloy Seals – NBR |